



Count on it.

## TimeCutter® SS4225, Model No. 75752TA



### TECHNICAL SPECIFICATIONS AND FEATURES

<b>Engine</b>	Kohler KT725-3097, 16.4 kW (22.0 hp) as per J1940, 725 cc, overhead valve, V-twin single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. Standard Kohler foam & paper element air cleaner. High idle speed set at 3,300 +/- 100 rpm.
<b>Construction</b>	Riveted and bolted 10 gauge steel.
<b>Deck Size</b>	106.7 cm (42.0 inch).
<b>Deck Configuration</b>	Right side discharge, two blade mid-mounted rotary. Drawn 13 gauge (2.28 mm) formed steel housing with welded mounting brackets. Frame supported. Left and right front mounted anti-scalp rollers.
<b>Deck Spindles</b>	Die cast aluminum spindle housing (2). Permanently lubricated sealed precision ball bearings. 17.0 mm (0.66inch) diameter spindle shaft.
<b>Height of Cut</b>	3.8 cm to 11.4 cm (1.5 to 4.5 inches) HOC in 7 increments.
<b>Hydro Drive Unit</b>	Dual Hydro-gear ZT-2100 hydrostatic transaxles, belt drive with self-tensioning system.
<b>Ground Speed</b>	<b>Mow:</b> 0 to 11.3 km/h (0 to 7.0 mph). <b>Trim:</b> 0 to 8.9 km/h (0 to 5.5 mph). <b>Tow:</b> 0 to 6.4 km/h (0 to 4.0 mph). <b>Reverse:</b> 0 to 4.4 km/h (0 to 3.5 mph).
<b>Wheel Base</b>	115.8 cm (45.6 inches) – centre of rear tyre to centre of front tyre.
<b>Steering Control</b>	Ergonomic, adjustable steering levers with heavy-duty dampeners.
<b>Width</b>	<b>Deflector Down:</b> 136.1 cm (53.6 inches). <b>Deflector Up:</b> 123.2 cm (48.5 inches).
<b>Overall Length</b>	185.4 cm (73.0 inches).
<b>Overall Height</b>	99.1 cm (39.0 inches).
<b>Tyres</b>	<b>Front:</b> 11 x 4.0-5.0, 2 ply, smooth tread, pneumatic. <b>Rear:</b> 18 x 7.5-8, 4 ply, turf tread, pneumatic.
<b>Fuel Tank Capacity</b>	11.4 litres (single tank).
<b>Net Weight</b>	240.4 kg (530.0 lbs.).
<b>Seat</b>	40.67 cm (16.0 inch) contoured seat, adjustable, hinged mounting, with spring suspension.
<b>Warranty</b>	<b>Consumer:</b> Machine 3 years, Engine & Transaxles 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). <b>Commercial:</b> Machine & Transaxles 30 days, Engine 3 years, Wear Parts (including belts & tyres) 90 days, Battery: 30 days. <b>Attachments:</b> 1 year. <b>NOTE:</b> Engine warranty is through Engineered Products Group (EPG) (Ph No. 1800 620 652). <i>For all other conditions, refer to the online The Toro Warranty statement.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

Issue Date: April 11, 2022

**PLEASE NOTE:** The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

## **ACCESSORIES AND ATTACHMENTS**

Product	Part No.
Twin Bagger Kit - 42 inch Stamped Deck	79410
Blowout Ring Kit	137-7048
Recycler Kit – 42 inch	137-7042
Hourmeter Kit	116-5461
ROPS Kit	79485
Slope Sensor Kit, TimeCutter	79486
Deck Maintenance Jack #	127-6666
Jack Mount Kit	140-2711
LED Light Kit	140-2056
Deck Foot Lift Assist Kit	140-2059

# Jack requires mount kit 140-2711 and cannot be used if Step Kit and Assist Handle is fitted.

Product	Part No.
Floor Mat Kit	140-2060
Seat Armrest Kit	140-2058
Seat Cover (W/O armrests)	117-0096
Assist Bar Kit	140-2052
Storage Cover	490-7516
Striping Kit – 42 inch	140-5198
Front Weight Kit	140-2050
Deluxe Seat Kit	140-2057
Caster Wheel Kit	145-0475

## **REGULAR MAINTANENCE ITEMS**

Product	Part No.
Air Cleaner Paper Element	32 083 09-S
Air Cleaner Foam Element	32 083 10-S
Engine Oil Filter	12 050 01-S
Engine Fuel Filter	25 050 22-S
Engine Valve Cover O-Ring (2 required)	24 153 30-S
Spark Plugs	Champion® XC12YC

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SJ or higher. Engine Oil SAE-30 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	With oil filter change – 1.9 litres
Transaxle Oil	SAE 20W-50 API Engine Oil
Transaxle Oil Capacity	1.6 to 1.65 litres per side

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	139-2399	Deck Plastic Discharge Deflector	137-7046
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Washout Port Fitting	133-9289
Traction Drive Assembly Idler Pulley	68-0030-03	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Engine Pulley	138-9792	Blade Attaching Screw	26-0671
Transaxle Pulley and Fan Kit	135-7349	Blade Attaching Screw Washer	3290-465
PTO Clutch	117-7468	Fuel Tank Cap	137-4119
Deck Spindle Housing	139-3214	Caster Wheel Tyre	140-2736
Deck Spindle Drive Belt	119-8819	Rear Tyre (Standard Tread)	139-7536
Deck Spindle Pulley	139-2433	Rear Tyre (Aggressive Tread)	140-2799
Deck Spindle Drive Belt Flat Idler Pulley	132-9420	Ignition Key	63-8360
Deck Spindle Shaft	117-7268	Battery (Dry)	105-1692
Deck Spindle Bearing (2 required)	138-9770	Throttle Cable	139-3267
Deck Belt Cover	108-7889	Choke Cable	139-2402

## **Blades**

Blade Type	Part No.
Standard and Bagger Application (Hi-Lift)	137-1999-03
Optional (Recycler / Mulch)	117-5376-03